

Chantaffiche™ 200 JE PET

Durchleuchtungspapier mit PET-Verstärkung für die Anwendung im Wechslerbetrieb |
Backlit paper with PET reinforcement for scrolling applications

Technisches Datenblatt | Technical data sheet

Flächenbezogene Masse:
Grammage: 150 g/m²

Ident-Nr.: 711838

Version: 04/2017

	Eigenschaft Characteristic	Methode Method	Einheit Unit	Typischer Wert Typical value	Toleranz Tolerance
1	Flächenbezogene Masse Grammage	DIN EN ISO 536	g/m ²	150	± 5
2	Dicke Thickness	DIN EN ISO 534	µm	150	± 10
3	CIE Weißgrad CIE Whiteness	ISO 11475	%	100	± 7
4	Opazität trocken Dry opacity	ISO 2471	%	98	± 1

Kontakt / Contact:

KÄMMERER Paper GmbH

Römereschstraße 33

Phone +49 541 604-832

heike.ehrlich@kaemmerer-paper.com

D-49090 Osnabrück

www.kaemmerer-paper.com

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed, including without limitation any warranty of merchantability and fitness for use. All users of the material are responsible for assuring that it is suitable for their needs, environment and end use. All data is subject to change as KÄMMERER Paper GmbH deems appropriate. Refer to www.kaemmerer-paper.com for contact information.