## **TECHNICAL DATA SHEET**

Grade: Swiss Matt 971

g/m<sup>2</sup>: 90/100/120/140/180

Characteristics: • Coated inkjet paper suitable for dye, pigmented, solvent, eco-solvent and oil-

based inks.

**Applications:** • Final CAD renderings

· Graphic presentations

• Indoor short term promotions

**Advantages:** • Enhanced smoothness

• Excellent line-sharpness

Excellent waterresistance

Suitable ink systems:

dye pigmented eco mild hard UV curable

solvent solvent solvent

Availability: Plotter reels

90/100 g/m<sup>2</sup>

Width Zoll	Length Yds.	Width cm	Length m	Core Zoll	Qty rolls / pallet		
24	49	61.0	45	2"	126		
24	49	61.0	45	2"	84	6 reels / box	
24.6	49	62.5	45	2"	96		
36	49	91.4	45	2"	84		
36	49	91.4	45	2"	48	4 reels / box	
42	49	106.7	45	2"	63		
50	49	127.0	45	2"	63		
54	49	137.2	45	2"	63		
60	49	152.4	45	2"	63		
36	98	91.4	90	2"	42		
Other sizes available upon request.							

**Availability:** Plotter reels 120 g/m<sup>2</sup>

Width Zoll	Length Yds.	Width cm	Length m	Core Zoll	Qty rolls / pallet
24	33	61.0	30	2"	189
24.6	33	62.5	30	2"	96
36	33	91.4	30	2"	84
42	33	106.7	30	2"	63
50	33	127.0	30	2"	63
54	33	137.2	30	2"	63
60	33	152.4	30	2"	63
24	98	61.0	90	2"	24
36	98	91.4	90	2"	24
Other sizes av	ailable upon reque	est.	<del>-</del>	<del></del>	<u> </u>

Important: The information given is based on our best knowledge at the time of printing. It is given in good faith and represents neither implied nor actual guarantee and no legal warranty for specific properties or for suitability for a specific application. Responsibility for testing the suitability of the product for specific applications lies with the purchaser. We shall be pleased to aid customers with such tests where possible. Should a claim be taken into consideration, liability will, under no circumstances exceed the value of the goods supplied. Cham Paper Group guarantees the impeccable quality of its goods in accordance with agreed specifications and their standard conditions of sale and delivery.

**Availability:** Plotter reels 140/180 g/m<sup>2</sup>

Width	Length	Width	Length	Core	Qty rolls / pallet	
Zoll	Yds.	cm	m	Zoll		
24	33	61.0	30	2"	189	
36	33	91.4	30	2"	84	
42	33	106.7	30	2"	63	
50	33	127.0	30	2"	63	
54	33	137.2	30	2"	63	
60	33	152.4	30	2"	63	
Other sizes available upon request.						

## **Specifications:**

Target values at 23 ℃ / 50% r.H. for General guidance only	Methods	Units					
Substance	DIN ISO 536	g/m²	90.0	100.0	120.0	140.0	180.0
Thickness	DIN 53105 T1	μm	105.0	120.0	145.0	170.0	210.0
Whiteness CIE	DIN 53145/2	%	155.0	155.0	155.0	155.0	155.0
Opacity	DIN 53146	%	92.0	93.0	94.0	96.0	98.0
Roughness PPS H10 WS	DIN ISO 8791-4	μm*100	550.0	550.0	550.0	550.0	550.0
L* WS	DIN 6174		94.8	94.8	94.8	94.8	94.8
a* WS	DIN 6174		3.0	3.0	3.0	3.0	3.0
b* WS	DIN 6174		- 15.0	- 15.0	- 15.0	- 15.0	- 15.0

The paper should be fed into the inkjet printer according to the printer instructions for use .The paper should be protected from moisture. Avoid marking the paper with fingerprints. A relative humidity of over 60% can affect the picture quality. Printouts with pigmented inks should be protected from smudging for a short time until the pigments have completely anchored themselves in the coating layer.

Edition: April 09

Important: The information given is based on our best knowledge at the time of printing. It is given in good faith and represents neither implied nor actual guarantee and no legal warranty for specific properties or for suitability for a specific application. Responsibility for testing the suitability of the product for specific applications lies with the purchaser. We shall be pleased to aid customers with such tests where possible. Should a claim be taken into consideration, liability will, under no circumstances exceed the value of the goods supplied. Cham Paper Group guarantees the impeccable quality of its goods in accordance with agreed specifications and their standard conditions of sale and delivery.