

OPAL color range light transmission (%)*

PLAZIT CAT number	1	2	3	4	5	6	8	10	12	15	20
R7001			50-51								
R7003											
R7004		30-34	30-34	28-32							
R7005		27-31	27-31	25-29	24-28						
R7007		45-48	45-48								
R7076			88-90								
R7361			60-64	58-62							
R7062		22-25	21-24	17-21	15-19						
R7063	37	38-40	37-39	35-37	33-35	32-34	27-29	22-24		12-14	5-7
R7064		29-31	29-31	26-29	25-28	25-28	19-23	18-21	15-17		
R7065		23-27	23-27	23-26	21-25	20-24					
R7066	6-8	6-8	5-7	5-7	4-6	4-6	0-5	0-5		0-5	
R7067		7-9	6-8	6-8	5-7	4-6	0-5	0-5		0-5	
R7068	40-43	39-43	38-42	35-38	31-35	30-34	27-29	21-24			
R7069	77-79	81-83	78-81	77-79	77-79	77-79	76-78	77-80			
R7070		84-86	83-85								
R7072		69-72	65-69	62-65	60-63						
R8072		74-77	67-69	65-67	44-47	41-44	28-30				
R8080	45-50	37-40	22-25	12-15	12-14	7-9	5-8	3-5			
R4567		80-82	80-82	77-79	77-79	77-79					
R4586		10-13	10-13	10-13	10-13	10-13	10-13				
R1086		32-36	30-34	29-32	28-31	28-31					

* Light Transmission measurement for all products according to ASTM D-1003 measured by Hazegard Plus - BYK Gardner

last updated 19.06.2014

